



	DES	DESE
Cilindro serratura	Universale	Europeo
N° posizioni	2 ± 90°	2 ± 90°
Grado di protezione	IP54	IP54
Tipo contatti	Nc+No	Nc+No
Portata max contatti	<2A;<42V a.c./d.c.	
Temperatura min/max	-20 +55 °C	-20 +55 °C
Dimensione mm	65x80x40	65x80x40



	DIXES	DIX
Descrizione	Selettore	Decoder
Alimentazione	12÷20V d.c.	12÷24V a.c.
Assorbimento max	50 mA	50 mA
Grado di protezione	IP54	IP30
N° tipo contatti		- 4 x No
Portata max contatti	-	- 50 x 50 mA
Temperatura min/max	-20 +55°C	-20 +55°C
Dimensione mm	65x83x41	77x59x24



	DES	DESE
Cylinder bolt	Universale	Europeo
N° positions	2 ± 90°	2 ± 90°
Protection level	IP54	IP54
Contacts type	Nc+No	Nc+No
Reach max contacts	<2A;<42V a.c./d.c.	
Temperature min/max	-20 +55 °C	-20 +55 °C
Dimension mm	65x80x40	65x80x40

## DES-DESE

### Key selectors.

Code Description

DES Key selectors. Normal bolt. External application. Aluminium casing.

DIN Key selectors. Normal bolt. External application. Wall-mount application to be combined with AREC box.

DESE Key selectors. European bolt. External application. Aluminium casing.

DINE Key selectors. European bolt. Aluminium casing. Wall-mount application to be combined with AREC box.

AREC Wall-insert box for photocells, selector and digital keyboards. (Pcs/Box 10)

AREF Supporting bracket for photocells, selectors and digital keyboards. (Pcs/Box 4)

ALED Indication light for key selectors. (Pcs/Box 5)

ALEP Fixing interface for photocells, selectors and digital keyboards when different wall fittings are in use. (Pcs/Box 4)

